

D01AJF – NAG Fortran Library Routine Document

Note. Before using this routine, please read the Users' Note for your implementation to check the interpretation of bold italicised terms and other implementation-dependent details.

1 Purpose

D01AJF is a general-purpose integrator which calculates an approximation to the integral of a function $f(x)$ over a finite interval $[a, b]$:

$$I = \int_a^b f(x) dx.$$

2 Specification

```

SUBROUTINE D01AJF(F, A, B, EPSABS, EPSREL, RESULT, ABSERR, W, LW,
1             IW, LIW, IFAIL)
  INTEGER      LW, IW(LIW), LIW, IFAIL
  real        F, A, B, EPSABS, EPSREL, RESULT, ABSERR, W(LW)
  EXTERNAL    F

```

3 Description

D01AJF is based upon the QUADPACK routine QAGS (Piessens *et al.* [3]). It is an adaptive routine, using the Gauss 10-point and Kronrod 21-point rules. The algorithm, described by de Doncker [1], incorporates a global acceptance criterion (as defined by Malcolm and Simpson [2]) together with the ϵ -algorithm (Wynn [4]) to perform extrapolation. The local error estimation is described by Piessens *et al.* [3].

The routine is suitable as a general purpose integrator, and can be used when the integrand has singularities, especially when these are of algebraic or logarithmic type.

D01AJF requires the user to supply a function to evaluate the integrand at a single point.

The routine D01ATF uses an identical algorithm but requires the user to supply a subroutine to evaluate the integrand at an array of points. Therefore D01ATF will be more efficient if the evaluation can be performed in vector mode on a vector-processing machine.

4 References

- [1] de Doncker E (1978) An adaptive extrapolation algorithm for automatic integration *SIGNUM Newsl.* **13** (2) 12–18
- [2] Malcolm M A and Simpson R B (1976) Local versus global strategies for adaptive quadrature *ACM Trans. Math. Software* **1** 129–146
- [3] Piessens R, de Doncker–Kapenga E, Überhuber C and Kahaner D (1983) *QUADPACK, A Subroutine Package for Automatic Integration* Springer-Verlag
- [4] Wynn P (1956) On a device for computing the $e_m(S_n)$ transformation *Math. Tables Aids Comput.* **10** 91–96

5 Parameters

- 1: F — *real* FUNCTION, supplied by the user. *External Procedure*
 F must return the value of the integrand f at a given point.
 Its specification is:

<pre style="margin: 0;"> <i>real</i> FUNCTION F(X) <i>real</i> X 1: X — <i>real</i> <i>Input</i> <i>On entry:</i> the point at which the integrand f must be evaluated.</pre>

F must be declared as EXTERNAL in the (sub)program from which D01AJF is called. Parameters denoted as *Input* must **not** be changed by this procedure.

- 2: A — *real* *Input*
On entry: the lower limit of integration, a .
- 3: B — *real* *Input*
On entry: the upper limit of integration, b . It is not necessary that $a < b$.
- 4: EPSABS — *real* *Input*
On entry: the absolute accuracy required. If EPSABS is negative, the absolute value is used. See Section 7.
- 5: EPSREL — *real* *Input*
On entry: the relative accuracy required. If EPSREL is negative, the absolute value is used. See Section 7.
- 6: RESULT — *real* *Output*
On exit: the approximation to the integral I .
- 7: ABSERR — *real* *Output*
On exit: an estimate of the modulus of the absolute error, which should be an upper bound for $|I - \text{RESULT}|$.
- 8: W(LW) — *real* array *Output*
On exit: details of the computation, as described in Section 8.
- 9: LW — INTEGER *Input*
On entry: the dimension of the array W as declared in the (sub)program from which D01AJF is called. The value of LW (together with that of LIW below) imposes a bound on the number of sub-intervals into which the interval of integration may be divided by the routine. The number of sub-intervals cannot exceed LW/4. The more difficult the integrand, the larger LW should be.
Suggested value: a value in the range 800 to 2000 is adequate for most problems.
Constraint: $LW \geq 4$.
- 10: IW(LIW) — INTEGER array *Output*
On exit: IW(1) contains the actual number of sub-intervals used. The rest of the array is used as workspace.

11: LIW — INTEGER *Input*

On entry: the dimension of the array IW as declared in the (sub)program from which D01AJF is called. The number of sub-intervals into which the interval of integration may be divided cannot exceed LIW.

Suggested value: $LIW = LW/4$.

Constraint: $LIW \geq 1$.

12: IFAIL — INTEGER *Input/Output*

On entry: IFAIL must be set to 0, -1 or 1. Users who are unfamiliar with this parameter should refer to Chapter P01 for details.

On exit: IFAIL = 0 unless the routine detects an error or gives a warning (see Section 6).

For this routine, because the values of output parameters may be useful even if IFAIL \neq 0 on exit, users are recommended to set IFAIL to -1 before entry. **It is then essential to test the value of IFAIL on exit.**

6 Error Indicators and Warnings

If on entry IFAIL = 0 or -1, explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors or warnings specified by the routine:

IFAIL = 1

The maximum number of subdivisions allowed with the given workspace has been reached without the accuracy requirements being achieved. Look at the integrand in order to determine the integration difficulties. If the position of a local difficulty within the interval can be determined (e.g., a singularity of the integrand or its derivative, a peak, a discontinuity, etc.) you will probably gain from splitting up the interval at this point and calling the integrator on the subranges. If necessary, another integrator, which is designed for handling the type of difficulty involved, must be used. Alternatively, consider relaxing the accuracy requirements specified by EPSABS and EPSREL, or increasing the amount of workspace.

IFAIL = 2

Round-off error prevents the requested tolerance from being achieved. The error may be underestimated. Consider requesting less accuracy.

IFAIL = 3

Extremely bad local integrand behaviour causes a very strong subdivision around one (or more) points of the interval.

IFAIL = 4

The requested tolerance cannot be achieved, because the extrapolation does not increase the accuracy satisfactorily; the returned result is the best which can be obtained. The same advice applies as in the case of IFAIL = 1.

IFAIL = 5

The integral is probably divergent, or slowly convergent. Please note that divergence can occur with any non-zero value of IFAIL.

IFAIL = 6

On entry, $LW < 4$,
or $LIW < 1$.

7 Accuracy

The routine cannot guarantee, but in practice usually achieves, the following accuracy:

$$|I - \text{RESULT}| \leq \text{tol},$$

where

$$\text{tol} = \max\{|\text{EPSABS}|, |\text{EPSREL}| \times |I|\},$$

and EPSABS and EPSREL are user-specified absolute and relative error tolerance. Moreover it returns the quantity ABSERR which, in normal circumstances, satisfies

$$|I - \text{RESULT}| \leq \text{ABSERR} \leq \text{tol}.$$

8 Further Comments

The time taken by the routine depends on the integrand and the accuracy required.

If IFAIL \neq 0 on exit, then the user may wish to examine the contents of the array W, which contains the end-points of the sub-intervals used by D01AJF along with the integral contributions and error estimates over the sub-intervals.

Specifically, for $i = 1, 2, \dots, n$, let r_i denote the approximation to the value of the integral over the sub-interval $[a_i, b_i]$ in the partition of $[a, b]$ and e_i be the corresponding absolute error estimate.

Then, $\int_{a_i}^{b_i} f(x) dx \simeq r_i$ and $\text{RESULT} = \sum_{i=1}^n r_i$, unless D01AJF terminates while testing for divergence of the integral (see Piessens *et al.* [3], Section 3.4.3). In this case, RESULT (and ABSERR) are taken to be the values returned from the extrapolation process. The value of n is returned in IW(1), and the values a_i, b_i, e_i and r_i are stored consecutively in the array W, that is:

$$\begin{aligned} a_i &= W(i), \\ b_i &= W(n+i), \\ e_i &= W(2n+i) \text{ and} \\ r_i &= W(3n+i). \end{aligned}$$

9 Example

To compute

$$\int_0^{2\pi} \frac{x \sin(30x)}{\sqrt{\left(1 - \left(\frac{x}{2\pi}\right)^2\right)}} dx.$$

9.1 Program Text

Note. The listing of the example program presented below uses bold italicised terms to denote precision-dependent details. Please read the Users' Note for your implementation to check the interpretation of these terms. As explained in the Essential Introduction to this manual, the results produced may not be identical for all implementations.

```
*      D01AJF Example Program Text
*      Mark 14 Revised.  NAG Copyright 1989.
*      .. Parameters ..
      INTEGER          LW, LIW
      PARAMETER        (LW=800,LIW=LW/4)
      INTEGER          NOUT
      PARAMETER        (NOUT=6)
*      .. Scalars in Common ..
      real            PI
      INTEGER          KOUNT
*      .. Local Scalars ..
      real            A, ABSERR, B, EPSABS, EPSREL, RESULT
```

```

      INTEGER          IFAIL
*    .. Local Arrays ..
      real            W(LW)
      INTEGER          IW(LIW)
*    .. External Functions ..
      real            FST, X01AAF
      EXTERNAL         FST, X01AAF
*    .. External Subroutines ..
      EXTERNAL         D01AJF
*    .. Common blocks ..
      COMMON           /TELNUM/PI, KOUNT
*    .. Executable Statements ..
      WRITE (NOUT,*) 'D01AJF Example Program Results'
      PI = X01AAF(PI)
      EPSABS = 0.0e0
      EPSREL = 1.0e-04
      A = 0.0e0
      B = 2.0e0*PI
      KOUNT = 0
      IFAIL = -1
*
      CALL D01AJF(FST,A,B,EPSABS,EPSREL,RESULT,ABSERR,W,LW,IW,LIW,IFAIL)
*
      WRITE (NOUT,*)
      WRITE (NOUT,99999) 'A      - lower limit of integration = ', A
      WRITE (NOUT,99999) 'B      - upper limit of integration = ', B
      WRITE (NOUT,99998) 'EPSABS - absolute accuracy requested = ',
+ EPSABS
      WRITE (NOUT,99998) 'EPSREL - relative accuracy requested = ',
+ EPSREL
      WRITE (NOUT,*)
      IF (IFAIL.NE.0) WRITE (NOUT,99996) 'IFAIL = ', IFAIL
      IF (IFAIL.LE.5) THEN
        WRITE (NOUT,99997) 'RESULT - approximation to the integral = ',
+ RESULT
        WRITE (NOUT,99998) 'ABSERR - estimate of the absolute error = '
+ ABSERR
        WRITE (NOUT,99996) 'KOUNT  - number of function evaluations = '
+ KOUNT
        WRITE (NOUT,99996) 'IW(1)  - number of subintervals used = ',
+ IW(1)
      END IF
      STOP
*
      99999 FORMAT (1X,A,F10.4)
      99998 FORMAT (1X,A,e9.2)
      99997 FORMAT (1X,A,F9.5)
      99996 FORMAT (1X,A,I4)
      END
*
      real FUNCTION FST(X)
*    .. Scalar Arguments ..
      real      X
*    .. Scalars in Common ..
      real      PI
      INTEGER    KOUNT
*    .. Intrinsic Functions ..
      INTRINSIC SIN, SQRT

```

```
*      .. Common blocks ..  
COMMON          /TELNUM/PI, KOUNT  
*      .. Executable Statements ..  
KOUNT = KOUNT + 1  
FST = X*SIN(30.0e0*X)/SQRT(1.0e0-X**2/(4.0e0*PI**2))  
RETURN  
END
```

9.2 Program Data

None.

9.3 Program Results

D01AJF Example Program Results

```
A      - lower limit of integration =    0.0000  
B      - upper limit of integration =    6.2832  
EPSABS - absolute accuracy requested =  0.00E+00  
EPSREL - relative accuracy requested =  0.10E-03  
  
RESULT - approximation to the integral = -2.54326  
ABSERR - estimate of the absolute error =  0.13E-04  
KOUNT  - number of function evaluations =  777  
IW(1)  - number of subintervals used =   19
```
