

F04ZCF – NAG Fortran Library Routine Document

Note. Before using this routine, please read the Users' Note for your implementation to check the interpretation of bold italicised terms and other implementation-dependent details.

1 Purpose

F04ZCF estimates the 1-norm of a complex matrix without accessing the matrix explicitly. It uses reverse communication for evaluating matrix-vector products. The routine may be used for estimating matrix condition numbers.

2 Specification

```
SUBROUTINE F04ZCF(ICASE, N, X, ESTNRM, WORK, IFAIL)
INTEGER          ICASE, N, IFAIL
real           ESTNRM
complex       X(N), WORK(N)
```

3 Description

This routine computes an estimate (a lower bound) for the 1-norm

$$\|A\|_1 = \max_{1 \leq j \leq n} \sum_{i=1}^n |a_{ij}| \quad (1)$$

of an n by n complex matrix $A = (a_{ij})$. The routine regards the matrix A as being defined by a user-supplied 'Black Box' which, given an input vector x , can return either of the matrix-vector products Ax or $A^H x$, where A^H is the complex conjugate transpose. A reverse communication interface is used; thus control is returned to the calling program whenever a matrix-vector product is required.

Note. That this routine is **not recommended** for use when the elements of A are known explicitly; it is then more efficient to compute the 1-norm directly from the formula (1) above.

The **main use** of the routine is for estimating $\|B^{-1}\|_1$, and hence the **condition number** $\kappa_1(B) = \|B\|_1 \|B^{-1}\|_1$, without forming B^{-1} explicitly ($A = B^{-1}$ above).

If, for example, an LU factorization of B is available, the matrix-vector products $B^{-1}x$ and $(B^{-1})^H x$ required by F04ZCF may be computed by back- and forward-substitutions, without computing B^{-1} .

The routine can also be used to estimate 1-norms of matrix products such as $A^{-1}B$ and ABC , without forming the products explicitly. Further applications are described by Higham [2].

Since $\|A\|_\infty = \|A^H\|_1$, F04ZCF can be used to estimate the ∞ -norm of A by working with A^H instead of A .

The algorithm used is based on a method given by Hager [1] and is described by Higham [2]. A comparison of several techniques for condition number estimation is given by Higham [3].

4 References

- [1] Hager W W (1984) Condition estimates *SIAM J. Sci. Statist. Comput.* **5** 311–316
- [2] Higham N J (1988) FORTRAN codes for estimating the one-norm of a real or complex matrix, with applications to condition estimation *ACM Trans. Math. Software* **14** 381–396
- [3] Higham N J (1987) A survey of condition number estimation for triangular matrices *SIAM Rev.* **29** 575–596

5 Parameters

Note. This routine uses **reverse communication**. Its use involves an initial entry, intermediate exits and re-entries, and a final exit, as indicated by the **parameter ICASE**. Between intermediate exits and re-entries, **all parameters other than X must remain unchanged**.

- 1:** ICASE — INTEGER *Input/Output*
On initial entry: ICASE must be set to 0.
On intermediate exit: ICASE = 1 or 2, and $X(i)$, for $i = 1, 2, \dots, n$, contain the elements of a vector x . The calling program must
- (a) evaluate Ax (if ICASE = 1) or $A^H x$ (if ICASE = 2), where A^H is the complex conjugate transpose;
 - (b) place the result in X; and,
 - (c) call F04ZCF once again, with all the other parameters unchanged.
- On final exit:* ICASE = 0.
- 2:** N — INTEGER *Input*
On initial entry: n , the order of the matrix A .
Constraint: $N \geq 1$.
- 3:** X(N) — **complex** array *Input/Output*
On initial entry: X need not be set.
On intermediate exit: X contains the current vector x .
On intermediate re-entry: X must contain Ax (if ICASE = 1) or $A^H x$ (if ICASE = 2).
On final exit: the array is undefined.
- 4:** ESTNRM — **real** *Output*
On final exit: an estimate (a lower bound) for $\|A\|_1$.
- 5:** WORK(N) — **complex** array *Input/Output*
On initial entry: WORK need not be set.
On final exit: WORK contains a vector v such that $v = Aw$ where $ESTNRM = \|v\|_1 / \|w\|_1$ (w is not returned). If $A = B^{-1}$ and ESTNRM is large, then v is an approximate null vector for B .
- 6:** IFAIL — INTEGER *Input/Output*
On entry: IFAIL must be set to 0, -1 or 1. For users not familiar with this parameter (described in Chapter P01) the recommended value is 0.
On exit: IFAIL = 0 unless the routine detects an error (see Section 6).

6 Error Indicators and Warnings

If on entry IFAIL = 0 or -1, explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors detected by the routine:

IFAIL = 1

On entry, $N < 1$.

7 Accuracy

In extensive tests on **random** matrices of size up to $n = 100$ the estimate ESTNRM has been found always to be within a factor eleven of $\|A\|_1$; often the estimate has many correct figures. However, matrices exist for which the estimate is smaller than $\|A\|_1$ by an arbitrary factor; such matrices are very unlikely to arise in practice. See Higham [2] for further details.

8 Further Comments

8.1 Timing

The total time taken by the routine is proportional to n . For most problems the time taken during calls to F04ZCF will be negligible compared with the time spent evaluating matrix-vector products between calls to F04ZCF.

The number of matrix-vector products required varies from 5 to 11 (or is 1 if $n = 1$). In most cases 5 products are required; it is rare for more than 7 to be needed.

8.2 Overflow

It is the responsibility of the user to guard against potential overflows during evaluation of the matrix-vector products. In particular, when estimating $\|B^{-1}\|_1$ using a triangular factorization of B , F04ZCF should not be called if one of the factors is exactly singular – otherwise division by zero may occur in the substitutions.

8.3 Use in Conjunction with NAG Fortran Library Routines

To estimate the 1-norm of the inverse of a matrix A , the following skeleton code can normally be used:

```

... code to factorize A ...
IF (A is not singular) THEN
  ICASE = 0
10  CALL F04ZCF (ICASE,N,X,ESTNRM,WORK,IFAIL)
  IF (ICASE.NE.0) THEN
    IF (ICASE.EQ.1) THEN
      ... code to compute A(-1)x ...
    ELSE
      ... code to compute (A(-1)(H)) x ...

    END IF
    GO TO 10
  END IF
END IF

```

To compute $A^{-1}x$ or $(A^{-1})^H x$, solve the equation $Ay = x$ or $A^H y = x$ for y , overwriting y on x . The code will vary, depending on the type of the matrix A , and the NAG routine used to factorize A .

Note that if A is any type of **Hermitian** matrix, then $A = A^H$, and the code following the call of F04ZCF can be reduced to:

```

IF (ICASE.NE.0) THEN
  ... code to compute A(-1)x ...
  GO TO 10
END IF

```

The example program in Section 9 illustrates how F04ZCF can be used in conjunction with NAG Library routines for complex band matrices (factorized by F07BRF (CGBTRF/ZGBTRF)).

It is also straightforward to use F04ZCF for Hermitian positive-definite matrices, using F07FRF (CPOTRF/ZPOTRF), F06TFF and F07FSF (CPOTRS/ZPOTRS) for factorization and solution.

For upper or lower triangular matrices, no factorization routine is needed: $A^{-1}x$ and $(A^{-1})^H x$ may be computed by calls to F06SJF (CTRSV/ZTRSV) (or F06SKF (CTBSV/ZTBSV) if the matrix is banded, or F06SLF (CTPSV/ZTPSV) if the matrix is stored in packed form).

9 Example

To estimate the condition number $\|A\|_1 \|A^{-1}\|_1$ of the order 5 matrix

$$A = \begin{pmatrix} 1+i & 2+i & 1+2i & 0 & 0 \\ & 2i & 3+5i & 1+3i & 2+i \\ 0 & -2+6i & 5+7i & 6i & 1-i \\ 0 & 0 & 3+9i & 4i & 4-3i \\ 0 & 0 & 0 & -1+8i & 10-3i \end{pmatrix}$$

where A is a band matrix stored in the packed format required by F07BRFF (CGBTRF/ZGBTRF) and F07BSF (CGBTRS/ZGBTRS).

Further examples of the technique for condition number estimation in the case of *real* matrices can be seen in the example program section of F04YCF.

9.1 Program Text

Note. The listing of the example program presented below uses bold italicised terms to denote precision-dependent details. Please read the Users' Note for your implementation to check the interpretation of these terms. As explained in the Essential Introduction to this manual, the results produced may not be identical for all implementations.

```
*      F04ZCF Example Program Text
*      Mark 17 Revised.  NAG Copyright 1995.
*      .. Parameters ..
      INTEGER          NIN, NOUT
      PARAMETER       (NIN=5,NOUT=6)
      INTEGER          NMAX, KLMAX, KUMAX, LDA, LDX, NRHS
      PARAMETER       (NMAX=8, KLMAX=NMAX-1, KUMAX=NMAX-1,
+                    LDA=2*KLMAX+KUMAX+1, LDX=NMAX, NRHS=1)
*      .. Local Scalars ..
      real            ANORM, COND, ESTNRM
      INTEGER          I, ICASE, IFAIL, INFO, J, K, KL, KU, N
*      .. Local Arrays ..
      complex        A(LDA,NMAX), WORK(NMAX), X(LDX,NRHS)
      real           RWORK(1)
      INTEGER          IPIV(NMAX)
*      .. External Functions ..
      real           F06UBF
      EXTERNAL        F06UBF
*      .. External Subroutines ..
      EXTERNAL        F04ZCF, cgbtrf, cgbtrs
*      .. Intrinsic Functions ..
      INTRINSIC       MAX, MIN
*      .. Executable Statements ..
      WRITE (NOUT,*) 'F04ZCF Example Program Results'
*      Skip heading in data file
      READ (NIN,*)
      READ (NIN,*) N, KL, KU
      IF (N.LE.NMAX .AND. KL.LE.KLMAX .AND. KU.LE.KUMAX) THEN
         K = KL + KU + 1
         READ (NIN,*) ((A(K+I-J,J), J=MAX(I-KL,1), MIN(I+KU,N)), I=1,N)
*
*         First compute the 1-norm of A.
*
         ANORM = F06UBF('1-norm',N,KL,KU,A(KL+1,1),LDA,RWORK)
```

```

*
  WRITE (NOUT,*)
  WRITE (NOUT,99999) 'Computed norm of A =', ANORM
*
  Next estimate the 1-norm of inverse(A). We do not form the
  inverse explicitly.
  Factorise A into P*L*U.
*
  CALL cgbtrf(N,N,KL,KU,A,LDA,IPIV,INFO)
*
  ICASE = 0
  IFAIL = 0
20  CALL F04ZCF(ICASE,N,X,ESTNRM,WORK,IFAIL)
*
  IF (ICASE.EQ.0) THEN
    WRITE (NOUT,99999) 'Estimated norm of inverse(A) =', ESTNRM
  ELSE
    IF (ICASE.EQ.1) THEN
*
      Return X := inv(A)*X by solving A*Y = X, overwriting
      Y on X.
*
      CALL cgbtrs('No transpose',N,KL,KU,NRHS,A,LDA,IPIV,X,LDX,
+             INFO)
*
    ELSE IF (ICASE.EQ.2) THEN
*
      Return X := conjg(inv(A'))*X by solving conjg(A')*Y
      = X, overwriting Y on X.
*
      CALL cgbtrs('Conjugate transpose',N,KL,KU,NRHS,A,LDA,
+             IPIV,X,LDX,INFO)
*
    END IF
*
    Continue until ICASE is returned as 0.
    GO TO 20
  END IF
  COND = ANORM*ESTNRM
  WRITE (NOUT,99998) 'Estimated condition number of A =', COND
END IF
STOP
*
99999 FORMAT (1X,A,F8.4)
99998 FORMAT (1X,A,F6.1)
END

```

9.2 Program Data

F04ZCF Example Program Data

```

5 1 2                                     :Values of N, KL, KU
( 1.0, 1.0) ( 2.0, 1.0) ( 1.0, 2.0)
( 0.0, 2.0) ( 3.0, 5.0) ( 1.0, 3.0) ( 2.0, 1.0)
          (-2.0, 6.0) ( 5.0, 7.0) ( 0.0, 6.0) ( 1.0,-1.0)
                    ( 3.0, 9.0) ( 0.0, 4.0) ( 4.0,-3.0)
                                (-1.0, 8.0) (10.0,-3.0) :End of matrix A

```

9.3 Program Results

F04ZCF Example Program Results

Computed norm of A = 23.4875

Estimated norm of inverse(A) = 37.0391

Estimated condition number of A = 870.0
